



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04M 1/02	A1	(11) International Publication Number: WO 97/32424 (43) International Publication Date: 4 September 1997 (04.09.97)
---	-----------	---

(21) International Application Number: PCT/EP97/00910

(22) International Filing Date: 24 February 1997 (24.02.97)

(30) Priority Data:

96102988.1 28 February 1996 (28.02.96) EP

(34) Countries for which the regional or international application was filed: AT et al.

(71) Applicant (for all designated States except US): NOKIA MOBILE PHONES LIMITED [FI/FI]; P.O. Box 86, FIN-24101 Salo (FI).

(72) Inventors; and

(75) Inventors/Applicants (for US only): FUHRMANN, Thomas [DE/DE]; Buldergeist 48, D-48249 Dülmen (DE). WILKE, Annett [DE/DE]; Castropoer Strasse 205, D-44791 Bochum (DE). UMBACH, Dirk [DE/DE]; Rheinstrasse 48, D-45525 Hattingen (DE). BARNETT, Ricky, William [GB/GB]; 17 Kendals Close, Radlett, Hertfordshire WD7 8NQ (GB). JOHNSON, Terence [GB/GB]; 9 Marlborough Close, Fleet, Hampshire GU13 9HY (GB). MASON, Mark, Robert [GB/GB]; 5 The Sonnets, Gadebridge, Hemel Hempstead, Hertfordshire HP1 3RS (GB). SAMUELS, Bruce [GB/GB]; 26 Sandown Way, Greenham, Newbury, Berkshire RG14

7SV (GB). HORNE, Tony [GB/GB]; 56 Woodlands Road, Baughurst, Tadley, Hampshire RG26 5NP (GB).


(74) Agents: FRAIN, Timothy, John et al.; Nokia Mobile Phones, St. Georges Court, St. Georges Court, Camberley, Surrey GU15 3QZ (GB).

(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, ES, FI, FI (Utility model), GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).

Published

With international search report.

(54) Title: RADIOTELEPHONE



(57) Abstract

An electronic radiotelephone comprising: a first housing; a second housing releasably attachable to the first housing to meet with the first housing around the periphery of the radiotelephone; and retaining means comprising a cover, for holding the electronic components of the radiotelephone to the first housing when the second housing is released from attachment with the first housing.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

RADIOTELEPHONE

This invention relates to a radiotelephone.

It has become desirable to be easily able to replace housing parts of radiotelephones. For example, customers may want to replace a broken or scratched housing for repair purposes, or to change the appearance of a radiotelephone by replacing its housing with another of a different appearance. Also, there may be a need for radiotelephones to be supplied to dealers without being fully housed, so that the dealers can fit distinctive housings of their own before the radiotelephones are sold. Normally it is the user interface housing of the phone that is replaced in this way.

Normally, when housing parts of a phone, especially user interface housing parts, are removed the internal components of the phone become loose and/or exposed and there is a significant risk of them being damaged. This makes it risky for unskilled people to replace the phone's housing parts, or for phones to be shipped in a partially housed state.

According to the present invention from one aspect there is provided: an electronic radiotelephone comprising: a first housing; a second housing releasably attachable to the first housing to meet with the first housing around the periphery of the radiotelephone; and retaining means comprising a cover, for holding the electronic components of the radiotelephone to the first housing when the second housing is released from attachment with the first housing.

The cover may extend over all or some of the electronic components of the phone. If the cover does not extend over all the components then the retaining means may comprise further articles such as a circuit board or another cover. The cover preferably retains user interface components such as a microphone, a

speaker, a display or a keymat. The cover preferably has means to allow communication between the retained user interface components and a user - for example a transparent or translucent portion, a deformable portion or a hole or aperture. The cover may hold one or more seals behind it, preferably for sealing around user interface components and, most preferably, associated apertures.

The cover is preferably attachable to the first housing, either directly or via other components of the retaining means. The cover is most preferably releasably attachable - for example by spring clips.

The first and second housings preferably provide front and rear outer casings for the radiotelephone. The housings preferably meet around substantially all of the perimeter of the radiotelephone, although there may suitably be regions where they do not meet - for example to provide access to the interior of the phone (e.g. for connectors).

At least one user interface component may be held captive between the second housing and the retaining means when the second housing is attached to the first housing. That said component is preferably a component which is visible, most preferably over a substantial region of the surface of the radiotelephone, when the radiotelephone is assembled. The component is preferably a keymat.

The cover preferably holds a keymat and/or a member that provides at least one user-actuable key to the first housing.

According to the present invention from a second aspect there is provided an electronic device having a housing which has a housing wall with openings for control elements and/or display elements, characterised by attachment means for detachably connecting to the housing an external wall element which at least partially covers the housing wall, the external wall element having openings which are aligned with the openings in the housing wall.

When the housing wall provided with openings is covered by the external wall element, the openings provided in the housing wall and in the external wall element are preferably aligned with one another so that for example the push-button keys which may project through the openings can continue to be used even after the external wall element is fitted on to the housing wall and/or so that display elements which may be inserted into the openings can be read. This preferably also applies to microphones or loudspeakers which may be inserted into the openings - for example in the case of cordless telephones.

By means of either aspect of the invention, the electronics provided in the device may suitably be protected against access by the customer when the external appearance of the housing is modified. Then, if one external wall element is to be replaced by another in order to give the electronic device a new design there is a reduced risk of the electronics present in the housing being damaged when the external wall elements are interchanged, or of the user being subjected to danger by the electronics present inside the housing. The external wall elements could even be interchanged when an electronic device is operating.

According to an advantageous refinement of the invention, the external wall element can engage, at least partially, over further housing walls of the housing so that the design of the housing can be modified to an even greater extent or adapted to the wishes of the user to an even greater degree.

The profile of the external wall element can preferably follow the profile of the housing walls of the housing, for instance if emphasis is being placed not so much on the modification of the shape of the housing but on changing the colour or the type of material of the housing. Alternatively, the external wall elements can have different shapes (which can also deviate from one another to a greater degree) provided it is ensured that after the respective external wall elements have been connected to the housing respective openings in the fitted-

on external wall element and in the housing wall in question are aligned with one another.

The external wall element can preferably be of, for example, shell-shaped design so that it can be fitted for example with one edge on to a base which projects outwards beyond the side walls of the housing.

Any desired attachment means can be used to attach the external wall element to the housing of the electronic device, but attachment means with press-on/catch closure can preferably be used. They preferably ensure a secure connection between the external wall element and the housing and, moreover, can suitably be easily used without a special tool being required for them.

The present invention will now be described, by way of example, with reference to the accompanying drawings, in which:

figure 1 shows a radiotelephone of a first embodiment with its external wall element removed;

figure 2 shows the radiotelephone of figure 1 with the external wall element fitted;

figure 3 shows a view of the interior of housing 14 of the radiotelephone of figure 1;

figure 4 shows a cross-section through part of the housing of figure 3; and

figure 5 shows an exploded view of a second embodiment of the invention.

The invention is explained below with reference to two embodiments of mobile phone.

Figure 1 shows a mobile phone having a housing 1 with which a plate-shaped base element 2 and a shell-shaped housing element 3 are associated. The plate-

shaped based element 2 and the shell-shaped housing element 3 are connected to one another using screws (not illustrated) which project upward through openings 4 in the shell-shaped housing element 3 and are screwed into sockets (not illustrated) which are fixedly connected to the inside of the plate-shaped base element 2. Inside the housing 1 there is a carrier plate or circuit board for electronic components etc., attached in a suitable way.

The shell-shaped housing element 3 has a housing wall 5 which is disposed essentially parallel with the plate-shaped base element 2 and located at a distance therefrom and is integral with side walls 6 which are supported with their free or lower edge on the plate-shaped base element 2. In this arrangement, the plate-shaped base element 2 projects outwards beyond the side walls 6 by constant distance in its edge region so that a profile with an identical contour is obtained.

In the housing wall 5 there is a plurality of through-openings 7 through which components inside the housing 1 partially project. The through-openings 7 can be provided for, for example, push-button keys 8, a display device 9 or a loudspeaker device/microphone device 10. A corresponding through-opening may also be present in the rear side wall 6' for an aerial.

On each of the side walls 6 extending in the longitudinal direction of the housing 1 there are two attachment means 11, at a distance from one another, which are designed as push fit/catch closures. They are located in each case near the front and rear ends of the telephone. The attachment means 11 have a catch projection 12 which is biased outwards in a sprung fashion and can be pressed inwards into the housing 1 against the outwardly acting spring force by means of an externally accessible activation element 13. The attachment means serve to attach to the housing 1 an external wall element 14 which is fitted over the shell-shaped housing element 3 and is also of shell-shaped design.

The shell-shaped external wall element 14 which is illustrated in Figure 1 has approximately the same contour as the shell-shaped cover 3 but is designed in such a way that it can receive the shell-shaped housing element 3 in it. If the external wall element 14, which is designed as a thin-walled shell, is fitted on to the shell-shaped housing element 3, the shell-shaped external wall element 14 is supported with the free or downwardly pointing edge of its side walls on that part of the plate-shaped base element 2 which projects outwards beyond the shell-shaped housing element 3. Here, the wall thickness of the side walls of the shell-shaped external wall element 14 corresponds to the distance by which the edge of the plate-shaped base element 2 projects outwards beyond the side walls 6, 6' of the shell-shaped housing element 3. As a result, no step remains in the connection area between the shell-shaped external wall element 14 and the plate-shaped base element 2. The height of the side walls of the shell-shaped external wall element 14 can be selected such that the main face of the external wall element 14 comes to rest at a short distance from the housing wall 5 and as a result does not exert any pressure on the latter.

Openings 7', which are aligned with the openings 7 in the housing wall 5 of the shell-shaped housing element 3, are provided in the main face of the external wall element 14. Therefore, it is possible to continue to operate the telephone even when the external wall element 14 is fitted on to the shell-shaped housing element 3. At the same time, the push-button keys 8 can be of such a height that they also project outwards beyond the external wall element 14. Openings which are present in the external wall element 14 for the display device 9 and the loudspeaker device/microphone device 10 can be covered, for example by means of a transparent element 15 or a grille 16.

Figure 2 shows the cordless telephone or mobile phone in a state in which the shell-shaped external wall element 14 is fitted on to the shell-shaped housing element 3 and is detachably connected to the housing 1. On the internal faces of the long side walls of the external wall element 14 there are notches for the

catch projections 12 of the attachment means 11 so that the catch projections 12 engage in the notches as a result of the outwardly pressing spring force, and thus hold the external wall element on the housing 1. In this state, the activation elements 13 are also pushed outwards but only to such an extent that they do not project beyond the side edge of the plate-shaped base element 2 or of the external wall element 14. The activation elements 13 can extend here in a groove 17 in the upper face of the plate-shaped base element 2. If the activation elements 13 are pressed inwards, that is to say inwards along the groove 17, for example using a pointed object, they move the catch projections 12 correspondingly inwards along with them so that the said catch projections 12 disengage from the notches on the inside of the side walls 6 of the external wall element 14. The external wall element 14 can then be removed from the housing 1.

The external wall element 14 is fitted on to the housing 1 by simply pressing it on. The catch projections 12 then engage automatically in the notches.

Figure 5 shows an exploded view of another embodiment. The mobile phone of figure 5 has two outer housings 18, 19. The housings mate together around the periphery of the phone to enclose almost all of the phone's components.

The lower housing 18 has a rear recess 18a, to accommodate a first circuit board 20, and a front shelf 18b to provide support behind the phone's keypad. The circuit board 20 carries and connects together electronic components, including RF (radio frequency) components shielded within RF shields 21. A two-part connector 22 is provided to allow for push-fit electrical connection between circuit board 20 and a second circuit board 23. Circuit board 23 carries other electronic components, including a buzzer 24 (for generating a telephone ringing tone) and an electrical connector 25 (for allowing external connections to be made to the phone - for example to program the phone or connect an external antenna).

A microphone 26 fits in a recess 25a in the connector block. The microphone is surrounded by a rubber sleeve or an o-ring 27 to hold it securely, by friction, in the recess 25a. The microphone has concentric electrical connection pads on its lower surface to connect to spring fingers on the circuit board 23 underneath it irrespective of the microphone's orientation relative to the circuit board.

Circuit board 23 has a region 28 of exposed printed conductive zones for co-operating with conductive portions of keypad membrane 29 to provide a touch-sensitive keypad. When the membrane is fixed by adhesive to the circuit board flexible domed regions 29a of the membrane can be pressed to the circuit board to act as key switches for sensing pressure from a user. When the phone is fully assembled each domed region falls below one of the keys 24a of keymat 24 so that a user can actuate the key switches.

A translucent plastics frame 32 fits to the rear end of circuit board 23. The frame carries an LCD (liquid crystal display) unit 30 and a reflector 31. The frame defines a recess 32a dimensioned to receive a speaker 33. The speaker has sprung rear connectors which, when the phone is assembled and the speaker is pressed towards the circuit board connect to corresponding connection pads on the circuit board 23.

To assemble the phone, circuit board 23 is screwed by means of screws 40 to the rear housing 18, holding the circuit board 20 in place behind it in the recess 18a. Microphone 26 is inserted in recess 25a and held in place by the friction of its o-ring 27 against the walls of the recess; at the same time the connections to the microphone are made by the spring fingers. Membrane 29 is fixed by adhesive to the circuit board 23. The frame 32 is offered up to the rear end of circuit board 23 and display unit 30 is soldered to the circuit board 23 to make the connections to the display. Speaker 33 is then set in the corresponding

recess 32a, with its spring contacts against the speaker contact pads on circuit board 23.

Next gasket 34 is placed over the frame/display assembly to seal around the edges of the speaker 33 and display device 30. The gasket is formed of flexible rubber with sealing walls that surround holes 34a, 34b for the speaker and display device. The gasket also includes a projecting key portion 34c whose upper end, when the phone has been fully assembled, projects through hole 19a in the upper housing 19. The key portion is flexible and has a conductive coating of carbon ink on its lower end which can make contact with corresponding tracks on the circuit board 23 when the upper end of the key portion is pressed by a user.

A retaining frame 35 is then pushed into place over the gasket to hold the gasket, the speaker 33, the LCD unit 30 and the frame 32 to the circuit board 23. The frame 35 has a generally flat top surface 36 and side walls 37. The frame is stamped from aluminium sheet around 80µm thick. The top surface 36 of the frame has a hole 35a for the display, a hole 35b for the key portion 34a, a hole 35c for a locating pin 32b on the plastics frame 32 and a grille 35d of holes for the speaker 33. When the frame 35 is pushed into place it squeezes the speaker and the LCD unit between the circuit board 23 and the gasket 34. The side walls of the cover are forced out slightly and then spring back as clips 38, bent from the side walls 37, engage the lower surface of the circuit board 23. The frame 35 thus clips into place and by bending the walls outward again the cover can be removed if needed. The clips 38 then hold the frame to the circuit board 23 and by means of the frame the gasket, the display unit and the speaker are held to the circuit board 23. For security a screw 39 is then inserted through holes in the upper projection, the plastics frame 32, and the circuit board 23 and then into the lower housing 18.

The antenna 40 is screwed in place in the lower housing 18.

At this stage in the assembly process only two components of the phone are loose from the assembly mounted to the rear housing 18; the keymat 24 and the front 19 with its display window 41 fixed in place by adhesive. To complete the assembly process the keymat is sat on the membrane 29, the front housing is mated to the rear housing and the two are screwed together with screws 43.

The present invention may include any novel feature or combination of features disclosed herein either explicitly or implicitly or any generalisation thereof irrespective of whether or not it relates to the presently claimed invention or mitigates any or all of the problems addressed. In view of the foregoing description it will be evident to a person skilled in the art that various modifications may be made within the scope of the invention. For example, it will be appreciated that the invention may be applied to a wide range of electronic devices such as calculators and personal organizers as well as radiotelephones.

CLAIMS

1. An electronic radiotelephone comprising:
 - a first housing;
 - a second housing releasably attachable to the first housing to meet with the first housing around the periphery of the radiotelephone; and
 - retaining means comprising a cover, for holding the electronic components of the radiotelephone to the first housing when the second housing is released from attachment with the first housing.
2. An electronic radiotelephone as claimed in claim 1, wherein the second housing is a user interface housing of the radiotelephone.
3. An electronic radiotelephone as claimed in claim 1 or 2, wherein the retaining means comprises a circuit board of the radiotelephone.
4. An electronic radiotelephone as claimed in claim 3, wherein at least one key sensor is provided on an outer surface of the circuit board.
5. An electronic radiotelephone as claimed in claim 3 or 4, wherein the cover is arranged to hold components of the radiotelephone between it and the said circuit board.
6. An electronic radiotelephone as claimed in any of claims 3 to 5, wherein the cover is releasably engageable with the circuit board
7. An electronic radiotelephone as claimed in any preceding claim, wherein at least one user interface component is retained by the cover.

8. An electronic radiotelephone as claimed in claim 7, wherein the cover includes an aperture overlying at least one user interface component retained by the cover.

9. An electronic radiotelephone as claimed in any preceding claim, wherein a sealing member is retained by the cover.

10. An electronic radiotelephone as claimed in any preceding claim, comprising at least one key unit for user-actuation of a key sensor, and wherein when the second housing is released from attachment with the first housing the key unit is free to move with respect to the first housing.

11. An electronic radiotelephone as claimed in any preceding claim, comprising at least one key unit for user-actuation of a key sensor, and wherein when the second housing is attached to the first housing the key unit is sandwiched between the second housing and the key sensor.

12. An electronic radiotelephone as claimed in claim 10 or 11, wherein the key unit is a key mat.

13. An electronic radiotelephone as claimed in claim 11 or 12, wherein the key sensor comprises a membrane switch.

14. An electronic radiotelephone substantially as herein described with reference to the accompanying drawings.





Fig.2.



3/4

Fig.3.






Fig.4.





INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 97/00910

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 H04M1/02

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 H04M H04B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	WO 93 17513 A (MOTOROLA INC) 2 September 1993 see page 2, line 22 - line 31 see page 4, line 18 - line 25 see page 7, line 25 - page 16, line 3; figures 1-10	1,3-8
Y	---	
A	US 4 291 202 A (ADAMS ET AL) 22 September 1981 see column 2, line 18 - column 4, line 34; figures 1-9	1,3-8 10-14
A	---	
A	US 5 357 065 A (MITAMURA ET AL) 18 October 1994 see column 2, line 47 - column 3, line 40; figures 1,2	1,10-13

	-/--	

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of the actual completion of the international search

21 May 1997

Date of mailing of the international search report

18. 06. 97

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3016

Authorized officer

Delangue, P

INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 97/00910

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>US 4 124 785 A (SERETNY ET AL) 7 November 1978 see column 4, line 13 - line 61; figures 1-3 -----</p>	1,3-8

Information on patent family members

International Application No

PCT/EP 97/00910

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9317513 A	02-09-93	CA 2107770 A,C JP 6507230 T SK 115493 A US 5371791 A	22-08-93 11-08-94 11-05-94 06-12-94
US 4291202 A	22-09-81	CA 1142282 A	01-03-83
US 5357065 A	18-10-94	JP 6029677 A	04-02-94
US 4124785 A	07-11-78	CA 1082828 A CA 1090021 A	29-07-80 18-11-80